

Detectors and base accessories

Order-No. LKM933



Ventilation duct detector housing

- for loop
 - it is installed into ventilation systems and enables the extraction of an air sample which reaches the detector via the air-entrance pipe and the sampling chamber
 - delivery includes:
 - aspirating pipe with 210mm length
 - air pipe with 210mm length
 - PG-screwing
 - Technical specification:
 - air velocity: 1 m/s to 25 m/s
 - pipe diameter: 300mm to 1500mm
 - Operating temperature: 0°C to +60°C
 - Dimensions: 200 x 110 x 92 mm (without air pipe)
- Please note: for inserting optical smoke detectors SSD633C

Order-No. RAL933



Detector alarm indicating PA

- displays hidden detectors when its attached to that detector, surface mounting-version
- elegant housing, white, with red display lens.
- two LEDs for direct connection within the detector

Flame detectors

Order-No. FF711



UV flame detector

- conventional detector
- Ultra violet (UV) models have a quick and efficient response to flame.
- The detector has a wide field of vision of up to 120°.
- Fast response: 1-2 sec.
- Technical specification:
 - supply voltage: 12-30VDC
 - supply current: 3mA quiescent
 - relay contact rating: 1A @ 30VDC (resistive load)
 - field of view: up to 120°
 - spectral response (UV): 185 to 260 nm
 - operating temperature: -10°C to 60°C
 - relative humidity: 95% non condensing
 - weight: 150g (including base)

Note: complete with base

Not applied for VdS and LPCB