


## Magnetic door holders


Order-No. 1330



### Electromagnetic wall door release 50Kg

- wall mounting
  - provided with damping keeper plate
  - permanent version available
  - Technical specification:
    - operating voltage: 24VDC
    - operating current: 65mA
    - holding strength: 50 kg / 490 N
    - operating temperature: -10°C to 55°C
    - IP rating: IP40
    - dimensions: 65x65x36mm
    - weight: 540g
    - material: die-cast alu, white painting
- Wire connection


Order-No. 1335



### Electromagnetic wall door release 50Kg

- Same as 1330 with manual release button and terminal block connection


Order-No. 1340



### Electromagnetic wall door release 100Kg

- wall mounting
  - provided with damping keeper plate
  - permanent version available
  - Technical specification:
    - operating voltage: 24VDC
    - operating current: 100mA
    - holding strength: 100 kg / 980 N
    - operating temperature: -10°C to 55°C
    - IP rating: IP40
    - dimensions: 65x65x40.5mm
    - weight: 800g
    - material: die-cast alu, white painting
- Wire connection

Order-No. 1345



### Electromagnetic wall door release 100Kg

- Same as 1340 with manual release button and terminal block connection

**Order-No. 1365****Electromagnetic wall door release 25Kg**

- wall mounting
  - provided with damping keeper plate
  - damping keeper plate permanent magnet
  - Technical specification:
    - operating voltage: 24VDC
    - operating current: 250mA
    - holding strength: 25 kg / 245 N
    - operating temperature: -10°C to 55°C
    - IP rating: IP40
    - dimensions: 65x65x36mm
    - weight: 710g
    - material: die-cast alu, white painting
- Wire connection

**Order-No. 1350****Electromagnetic wall door release 50Kg**

- wall mounting
- double holding strength, selectable by user die-cast aluminum case
- release button and protection circuit
- provided with damping keeper plate
- permanent version available
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 34mA-65mA
  - holding strength: 25-50 kg / 245-490 N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 95x95x45mm
  - weight: 800g
  - material: die-cast alu, white painting

**Order-No. 1360****Electromagnetic wall door release 100Kg**

- wall mounting
- double holding strength, selectable by user die-cast aluminum case
- release button and protection circuit
- provided with damping keeper plate
- permanent version available
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 40mA-100mA
  - holding strength: 50-100 kg / 490-980 N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 95x95x50mm
  - weight: 1Kg
  - material: die-cast alu, white painting

Order-No. 1367

**Electromagnetic wall door release 25Kg**

- wall mounting
- provided with damping keeper plate
- damping keeper plate permanent magnet
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 250mA
  - holding strength: 25 kg / 245 N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 95x95x50mm
  - weight: 950g
  - material: die-cast alu, white painting

Order-No. 1369

**Electromagnetic floor door holder 50Kg**

- floor mounting
- aluminum structure
- holding strength 50Kg
- provided with damping keeper plate
- release button
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 65mA
  - holding strength: 50kg / 490N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 109x100x92mm
  - weight: 950g
  - material: alu, epoxy black painting

Order-No. 1370/15

**Electromagnetic door release with bracket 50Kg**

- floor, wall and ceiling-mounting
- aluminum structure
- holding strength 50Kg
- provided with damping keeper plate
- release button
- mounting height with 30 mm regulation
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 65mA
  - holding strength: 50kg / 490N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 180-210 h x120x120mm (other height available)
  - weight: 1.2Kg
  - material: alu, epoxy black painting

Order-No. 1370/30

**Electromagnetic door release with bracket 50Kg**

- Same as 1370/15 with height 330-360 mm

---

**Order-No. 1380/15****Electromagnetic door release with bracket 100Kg**

- floor, wall and ceiling-mounting
- aluminum structure
- holding strength 100Kg
- provided with damping keeper plate
- release button
- mounting height with 30 mm regulation
- Technical specification:
  - operating voltage: 24VDC
  - operating current: 100mA
  - holding strength: 100kg / 980N
  - operating temperature: -10°C to 55°C
  - IP rating: IP40
  - dimensions: 185-215 h x120x120mm (other height available)
  - weight: 1.43Kg
  - material: alu, epoxy black painting

---

**Order-No. 1380/30****Electromagnetic door release with bracket 100Kg**

- Same as 1380/15 with height 335-365 mm